

KENWOOD

Listen to the Future

NEXEDGE™

NX-200/300

NEXEDGE™ VHF/UHF Digital & FM Portable Radios

NXDN®

FleetSync®
by KENWOOD

● GENERAL FEATURES

- 5 W (136-174 MHz) Models
- 5 W (400-470, 450-520 MHz) Models
- 512 CH-GID / 128 Zones
- 12-Key Keypad Models
- 14 Character Alphanumeric Aliases
- Backlit Dot Matrix LCD
- 3-Digit Sub-Display
- Function/Status LCD Icons
- RSSI Indicator
- Date & 12/24 Hour Time Clock
- Transmit/Busy/Call Alert/Warn LED
- On/Off Volume Knob
- 16-Position Mechanical Selector
- 6 Front PF & Menu Keys
- 2 Side PF Keys
- Emergency/AUX Key
- 500 mW Speaker Audio
- VOX Ready
- Emergency Call Features
- Emergency Man-Down Option
- Lone Worker
- Multi-Language Display
- Programmable TX/RX Indication (On/Off)
- Special Alert Tone Patterns
- Time Out Timer
- Busy Channel Lockout
- LCD Battery Status Indicator
- Low Battery Alert
- Battery Saver
- Weather-sealed ACC Connector
- MIL-Spec Speaker Mic Options
- KMC-38GPS Speaker Mic Option
- KPG-111D Windows® FPU
- Flash Firmware Upgrading
- Front Panel Test & Tune
- Cloning
- MIL-STD-810 C/D/E/F
- MIL-STD "Driven-Rain"
- IP-54/55 Water & Dust Intrusion
- Easy Option Port
- PC Serial Interface
- SDM Manual Input¹
- Transparent Data Mode¹
- Intrinsically Safe Option
- VGS-1 Voice Guide/ Voice & GPS Data Storage Option

● DIGITAL – COMMON

- NXDN® Digital Air Interface
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- Over-the-Air Alias
- Paging Call
- Emergency Call
- All Group Call
- Status Messaging¹
- Remote Stun/Kill¹
- Remote Check¹

- Short & Long Data Messages¹
- GPS Location with Voice¹
- NXDN® Scrambler Included (Conventional: per CH)

● DIGITAL – CONVENTIONAL MODE

- 64 Radio Access Numbers (RAN)
- DTMF (Encode/Decode)
- Individual & Group Selective Call
- Mixed FM/Digital Operation

● DIGITAL – TRUNKING MODE

- Individual Private Call
- Group Call
- Broadcast Call
- Transmission Trunked Mode²
- Message Trunked Mode²
- Call Queuing with Priority²
- Call Queue Pre-emption²
- Late Entry (UID & GID)²
- 4 Priority Monitor ID's²
- Remote Group Add¹
- Failsoft Mode
- Multi-Site IP Network Compatible

● SCAN

- Single Zone / Multi-Zone / List Scan
- Dual Priority Scan (Conventional)

● FM MODES – GENERAL

- 25 & 12.5 kHz Channels
- FleetSync®/II
- DTMF Encode / Decode
- Companded Audio
- Voice Inversion Scrambler
- Encryption/ANI Board Control

● FM CONVENTIONAL ZONES

- QT / DQT
- Two-Tone Decode
- Single/Two-Tone Encode
- Call Key 1-6
- Operator Selectable Tone

● FM LTR® TRUNKED ZONES

- Kenwood LTR® Features

● FleetSync®/II (FM)

- PTT ID Digital ANI
- Selective Call & Group Call
- Status Messaging¹
- Emergency Status
- Caller ID Display
- Short Text Messages¹
- Power On/Off Status Messages¹
- Send/Display GPS (KMC-38GPS)¹
- PTT ID & Emergency GPS Reporting¹
- Status Message Block GPS Reporting¹



Options

■ KNB-47L

Li-Ion Battery
(1950mAh)



■ KNB-48L

Li-Ion Battery
(2550mAh)

■ KNB-50NC

Ni-MH Battery
(2000mAh) Intrinsicly Safe

■ KSC-32

Tri-Chemistry Rapid
Rate Charger



■ KSC-326

Rapid Rate Six Unit Charger
for Ni-Cd/Ni-MH/Li-Ion



■ KMC-41M

MIL-STD & IP 54/55
Speaker Microphone



■ KMC-38GPS

GPS Speaker
Microphone



■ KHS-11

Heavy Duty Earphone



■ KEP-1

Heavy Duty Earphone



■ KRA-22/23

VHF/UHF Helical Antenna



■ KRA-26/27

VHF/UHF Whip Antenna



■ KRA-16/17

VHF/UHF Stubby Antenna



■ KRA-25

VHF High Gain Antenna



■ KRA-28

VHF Broad
Band Antenna



■ VGS-1

Voice Guide
& Storage Unit



■ KBH-11

Belt Clip (2.5")



All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Main Specifications

| | | NX-200 | NX-300 |
|------------------------------|--------------------------|--|----------------------------------|
| GENERAL | | | |
| Frequency Range | Type 1 Type 2 | 136-174 MHz | 450-520 MHz 400-470 MHz |
| Number of Channels | | 512 | |
| Zones | | 128 | |
| Max. Channels per Zone | | 250 | |
| Channel Spacing | Analog Digital | 12.5 / 15 / 25 / 30 kHz 6.25 / 12.5 kHz | 12.5 / 25 kHz 6.25 / 12.5 kHz |
| Operating Voltage | | 7.5V DC ± 20% | |
| Battery Life (with KNB-48L) | 5-5-90 10-10-80 | Approx. 14.5 hours Approx. 9.0 hours | |
| Operating Temperature Range | | -22° F to +140° F (-30° C to +60° C) | |
| Frequency Stability | | ± 2.0 ppm | ± 1.0 ppm |
| Antenna Impedance | | 50 Ω | |
| Dimensions (W x H x D) | Projections not included | | |
| | Radio only | 2.28 x 5.02 x 1.63 in (58 x 127.5 x 41.3 mm) | |
| | with KNB-47L | 2.28 x 5.02 x 1.63 in (58 x 127.5 x 41.3 mm) | |
| | with KNB-48L | 2.28 x 5.02 x 1.91 in (58 x 127.5 x 48.5 mm) | |
| Weight (net) | Radio only | 8.82 oz (250 g) | |
| | with KNB-47L | 13.23 oz (375 g) | |
| | with KNB-48L | 14.29 oz (405 g) | |
| FCC ID | Type 1 Type 2 | ALH378400 | ALH378500 ALH378501 |
| IC Certification | Type 1 Type 2 | 282D-378400 | 282D-378500 282D-378501 |

| | | NX-200 | NX-300 |
|----------------------------|--|---|--------|
| RECEIVER | | | |
| Sensitivity | Digital @ 6.25kHz (3% BER) Digital @ 12.5kHz (3% BER) Analog (12 dB SINAD) | 0.20 μV 0.25 μV 0.25 μV | |
| Selectivity | Analog @ 25 kHz Analog @ 12.5 kHz | 72 dB 65 dB | |
| Intermodulation Distortion | Analog | 70 dB (±50,100 kHz) | |
| Spurious Response | Analog | 70 dB | |
| Audio Distortion | | Less than 3% | |
| Audio Output | | 500 mW / 8 Ω | |
| TRANSMITTER | | | |
| RF Power Output | | 5 W / 1 W | |
| Spurious Response | | 70 dB | |
| FM Hum & Noise | Analog @ 25 kHz Analog @ 12.5 kHz | 45 dB 40 dB | |
| Audio Distortion | | Less than 3% | |
| Modulation | | 16K0F3E, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D | |

Analog measurements made per TIA/EIA 603 and specifications shown are typical. Kenwood reserves the right to change specifications without prior notice or obligation.

FleetSync™ is a registered trademark of Kenwood Corporation.
LTR™ is a registered trademark of Transcript International.
AMBE+2™ is a trademark of Digital Voice Systems Inc.
Windows™ is a registered trademark of Microsoft Corporation.
NXDN™ is a trademark of Kenwood Corporation and Icom Inc.
NEXEDGE™ is a trademark of Kenwood Corporation.

Applicable MIL-STD & IP

| MIL Standard | MIL 810C Methods/Procedures | MIL 810D Methods/Procedures | MIL 810E Methods/Procedures | MIL 810F Methods/Procedures |
|--|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
| Low Pressure | 500.1/Procedure I | 500.2/Procedure I, II | 500.3/Procedure I, II | 500.4/Procedure I, II |
| High Temperature | 501.1/Procedure I, II | 501.2/Procedure I, II | 501.3/Procedure I, II | 501.4/Procedure I, II |
| Low Temperature | 502.1/Procedure I | 502.2/Procedure I, II | 502.3/Procedure I, II | 502.4/Procedure I, II |
| Temperature Shock | 503.1/Procedure I | 503.2/Procedure I | 503.3/Procedure I | 503.4/Procedure I, II |
| Solar Radiation | 505.1/Procedure I | 505.2/Procedure I | 505.3/Procedure I | 505.4/Procedure I |
| Rain | 506.1/Procedure I, II | 506.2/Procedure I, II | 506.3/Procedure I, II | 506.4/Procedure I, III |
| Humidity | 507.1/Procedure I, II | 507.2/Procedure II, III | 507.3/Procedure II, III | 507.4 |
| Salt Fog | 509.1/Procedure I | 509.2/Procedure I | 509.3/Procedure I | 509.4 |
| Dust | 510.1/Procedure I | 510.2/Procedure I | 510.3/Procedure I | 510.4/Procedure I, III |
| Vibration | 514.2/Procedure VIII, X | 514.3/Procedure I | 514.4/Procedure I | 514.5/Procedure I |
| Shock | 516.2/Procedure I, II, V | 516.3/Procedure I, IV | 516.4/Procedure I, IV | 516.5/Procedure I, IV |
| International Protection Standard | | | | |
| Dust & Water Protection | IP54/55 | | | |

footnotes from Front:

¹ Requires NX subscriber unit PC Serial Interface compatible software application (e.g Kenwood AVL & Dispatch Messaging software) or hardware (e.g. console).

² These trunked features are primarily system programming and operational dependent. Priority Monitor also requires NX subscriber settings.

Listen to the Future

Kenwood has always connected with people through sound. Now we want to expand the world of sound in ways that only Kenwood can, listening to our customers and to the pulse of the coming age as we head toward a future of shared discovery, inspiration and enjoyment.

Kenwood U.S.A. Corporation
Communications Sector Headquarters

3970 Johns Creek Court, Suite 100, Suwanee, GA 30024

Order Administration/Distribution

P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

Kenwood Electronics Canada Inc.
Canadian Headquarters and Distribution

6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8



www.kenwoodusa.com



ADS#11309 Printed in USA